

FELIX RUBBERS INTERNATIONAL



LITHIUM AP-LL 30000 GREASE

AP-LL 30000 GREASE is lithium soap grease which provides high performance and superior shear resistance, hence has better structural & mechanical stability. This grease has service life up to 30,000 kilometers in automotive bearing application under ideal road condition. It provides excellent lubrication and protection to the bearing parts over a wide temperature & pressure range, under normal as well as adverse mechanical conditions.

FLX

Benefits

- High drop point.
- Great lubrication capability.
- High service life.
- Excellent water resistance capabilities.
- Higher corrosion protective capabilities.



As per IS 7623-1993,NLGI-3 specifications.

500gm | 1 kg | 2 kg | 3kg 5 kg | 7 kg | 10 kg | 18 kg 50 kg | 180 kg M.S. Barrel

Packing Available

FLX

15w40 API CF4 MULTI GRADE ENGINE OIL

15w40 ENGINE OIL is high quality multigrade engine oil,meeting API-CF4 performance requirements,formulated from selected high quality base oils and additives,to suit petrol & diesel engines,operating under severe duty conditions Recommended for commercial road transport & off highway vehicles applications,power shift transmissions and mobile hydraulic systems.

Benefits

- Provides excellent protection against high temperature, engine deposits & ring groove carbon.
- Provides optimum film thickness & strength under severe operating conditions.
- Protects against formation of gums, varnish & resists oil thickening & filter plugging for long drain period.
- Provides fuel savings and prolonged engine life.

Performance Level

As per API Cf4,IS 13656-2002 & US Military MIL-L-2104 E Specifications.

Packing Available

1 Ltr | 3 Ltr | 3.5 Ltr 5 Ltr 7.5 Ltr | 10 Ltr 15 Ltr | 20 Ltr 50 Ltr | 210 Ltr M.S. Barrel

CALCIUM MP-3/ GCB GREASE

MP-3/ GCB GREASE is Calcium soap base water resistant grease of medium consistency,recommended for use in majority of wheel bearings,water pumps earth moving & industrial equipments operating at moderate temperature.

Benefits

- Excellent water resistant.
- Lasting qualities in spring shackles and steering connections.
- Acts as protective layer on exposed parts.
- Clings to bearing surfaces.



MP-3 Packing Available 500gm | 1 kg | 2 kg | 3kg 5 kg | 7 kg | 10 kg | 18 kg 50 kg | 180 kg M.S. Barrel

FLX

GCB Packing Available 10 kg | 18 kg | 50 kg 180 kg M.S. Barrel

FLX

Performance Level

As per IS 507-1993, NLGI-3 specifications.

HYDRAULIC OIL

Available in 32, 46, 68, 100, 150, Viscosity Grades.

HYDRAULIC OIL are premium quality oils recommended for hydraulic systems using gear, bearings, vane, radial & axial piston, pumps, chain drivers, compressors, vacuum pumps, mining machinery tools, circulation oil system etc. were anti-wear type hydraulic oils are recommended.



Benefits

- Right viscosity to satisfy the demands of different types of hydraulic pumps.
- High viscosity index to restrict viscosity changes under operating conditions.
- Good film strength and antiwear properties to minimise wear of pump
- Excellent corrosion resistance to prevent rusting and corrosion of metal parts.
- High chemical stability to ensure long and trouble free service life.

Performance Level

As per IS -10522-1983 (Reaffirmed 1993), US Steel No. 127 specifications.

Packing Available: 5 Ltr | 20 Ltr | 50 Ltr | 210 Ltr M.S. Barrel

GREASES

Calcium Grease
Sodium Grease
Lithium EP Grease
Lithium Poly Plus Grease
C.V. Joint Grease
Bentonite Moly Grease
Bentonite Grease
Chassis Grease

LUBRICANTS

Engine Oils
Gear Oils
Hydraulic Oils
Transmission Fluids
Break Fluids

FELIX RUBBERS INTERNATIONAL

48/6 Rachna, Sector 3, Vaishali, Ghaziabad-201010
Email: info@felixrubbers.com, www.felixrubbers.com
customercare no. 0120 4330024